DEVELOP



PRODUCTION PRINTING




Ineo 6136/6120


- Up to 7,940 A4 pages per hour

In the fast-growing, digital high-volume print market, in-house printers and graphic communications providers have to focus on building up their business by producing a wider range of high-volume jobs more eliciently. For that, they need the best performance available in the market. The Ineo 6136 series comprises three models, the fastest of which provides a maximum speed of 7,940 A4 pages per hour. Latest technologies guarante maximum uptime and outstanding black and white print quality. The superior product outline impresses with a comprehensive range of inline inishing options.

Ineo 6136/6120

YOUR ADVANTAGES WITH AccurioPress 6136/6136P/6120





Recommended configurations



Technical specifications

SYSTEM SPECIFICATIONS

Resolution	1,200 x 1,200 dpi
Paper weight	40–350 gsm
Duplex unit	Non-stack type; 40–300 gsm
Paper sizes	Min.: 95 x 139 mm
	Max.: 324 x 483 mm (with PF-710)
Maximum image area	314 x 483 mm (with PF-710)
Paper input capacity	Standard: 3,000 sheets
	Max.: 18,000 sheets
Paper output capacity	Max.: 15,000 sheets (plus sub trays)
Main unit dimensions (W x D x H)	990 x 910 x 1,454 mm
Main unit weight	396 kg

PRODUCTIVITY

Ineo 6136

A4 - max. per minute	136 ppm	
A3 - max. per minute	78 ppm	
SRA3 - max. per minute	74 ppm	
A4 - max. per hour	7,940 pph	
A3 - max. per hour	4,526 pph	
SRA3 - may nor hour	4 274 nnh	

Inoo 6120

120 ppm
70 ppm
66 ppm
7,034 pph
4,072 pph
3,846 pph

CONTROLLER

Embedded Konica Minolta Controller

SCANNED SDECIFICATIONS*

SCANNER OF LON ICATIONS	
Scan speed A4	Up to 240 ppm
Scan resolution	600 x 600 dpi
Scan modes	TWAIN scan; Scan-to-HDD; Scan-to-FTP;
	Scan-to-SMB; Scan-to-eMail
Scan formats	TIFF; PDF; Encrypted PDF; XPS;
	CompactPDF; JPEG

COPIER SPECIFICATIONS*

Stacking unit

Booklet making unit

Booklet making unit

Creasing unit for SD-513

Spine corner forming unit for SD-513

Slitting unit for SD-513

Perfect binding unit

Gradations	256 gradations
FCOT	Less than 2.6 sec. (A4 LEF)
Magnification	25-400%, in 0,1% steps
Multiple copies	1–9,999
ACCESSORIES	
Integrated Color Care unit	IQ-501
Air assist paper feed unit	PF-709
Pre-printed paper feed kit for PF-706	PP-701
Air suction paper feed unit	PF-710
Heating unit for PF-710	HT-506
Post Insertion unit	PI-PFU
Relay unit	RU-518
Humidification unit	HM-103
Multi (GBC) punching unit	GP-501
Relay unit	RU-510
Auto ring binding unit	GP-502
Folding and punching unit	FD-503

LS-506

SD-506

SD-513

CR-101

TU-503

FD-504 PB-503

. orroot britaining arm	. 2 000
Stapling unit	FS-532
Saddle stitch kit for FS-532	SD-510
Punch kit for FS-532	PK-522
Post inserter for FS-532	PI-502
Open Stacker	OT-510
Envelop fuser	EF-105
Mount kit for 3rd party	MK-737
Removable HDD Kit	RH-101 & HD-511
Watkiss PowerSquare™ 224KR	
Plockmatic	SD-500/SD-350
GBC Punch G2	

All specifications refer to A4-size paper of 80 gsm quality.
The support and availability of the listed specifications and functionalities varies depending on operating systems, applications and network protocols as well as network and system configurations.

The stated life expectancy of each consumable is based on specific operating conditions such as page coverage for a particular page size (5% coverage of A4).
The actual life of each consumable will vary depending on use and other printing variables including page coverage, page size, media type, continuous or intermittent printing, ambient temperature and humidity.

Some of the product illustrations contain optional accessories.
Specifications and accessories are based on the information available at the time of printing and are subject to change without notice.

Konica Minolta does not warrant that any prices or specifications mentioned will be error-free.
All brand and product names may be registered trademarks or trademarks of their respective holders and are hereby acknowledged.